



Black Line

Entry control for home and office

by Jantar



Power supply Spider W40 / Spider W40B-NET



Spider W40B / W40B-NET

- Power supply (40W) with optional battery backup or optional built-in TCP/IP communication converter, designed for use with controllers Lokus, Rex and Regis (when battery backup is requested)
- Spider W40 is sufficiently strong to power 4 standalone access controllers and 4 door strikes or 2 electromagnetic locks (max. load 2A)
- Optional battery (2.3Ah), mentioned as a backup power supply (normal operation of the Spider W40 or Spider W40B does not require an additional battery)
- Built-in electronics for charging the battery
- Connecting point for push button and door status switch
- Connecting point for door strike output
- 4 x 5A relay, which trigger together with door-strike output
- Built-in TCP/IP converter (Spider W40B-NET only)

TECHNICAL DATA

- **Dimensions: 180x180x80mm**
- **Operating voltage: 110-230V AC**
- **Output: 13,8V DC (40W, full time)**
- **Primary fuse: 250V 2,5A**
- **IP21 protection**
- **Door status and push button wiring connection points (for 4 standalone access controllers)**
- **Door strike output wiring connectors**
- **5A relays outputs**
- **Power consumption: up to 1 W + load**
- **Operating temperature: -20 to +40°C**
- **Humidity: 10-80%, non-condensing**
- **LED status notification**
- **Battery support (battery not included)**

ORDERING CODES

Code	Specification
SPIDER W40B	Power supply (40W)
SPIDER W40B-NET	Power supply (40W) with integrated RS-485 - TCP/IP communication converter